



PACKING 	INNER pcs	MASTER pcs
Blister	6	36



TECHNICAL DATA

Power supply	DRY BATTERIES
Power supply provided	NO
How many batteries are used	3
Battery type	AAA
Batteries provided	(NOT INCLUDED)
Maximum autonomy (h)	17
Lighting source	HIGH POWER LED
Light technology	CREE® XP-G2
Lighting power (W)	3
Lumen	200
Scope (m)	100
Light beam	FOCUS
LED lifespan (hours)	30.000
Switch	YES
IP Protection	IP67
Color	YELLOW
Country of origin	CHINA
Material	PLASTIC - ABS
Warranty	2 YEARS
Width (mm)	80
Depth (mm)	45
Height (mm)	50
Net weight (Kg)	0.140

DESCRIPTION

ATEX: ii 1g ex ia iic t4 IP67. High power LED 200 lumens. IP67. Intrinsically safe flashlight for use in hazardous environments.





LOGISTICS DATA

Packing type	Blister
Blister pack format	F6
Pack length (mm)	60
Pack width (mm)	100
Pack height (mm)	320
Packed product weight (kg)	0.200
Inner width (cm)	42
Inner length (cm)	20

LOGISTICS DATA

Inner height (cm)	11
Quantity in inner	6
Gross weight inner (kg)	1.200
ITF INNER	18003910902746
Master length (cm)	34
Master width (cm)	42
Master height (cm)	37
Quantity in master	36
Master gross weight (kg)	7.230
ITF MASTER	28003910902743
How many pieces on 80x120 pallet (pz)	540
INTRASTAT Code	85131000
DEEE	0.02
ECOLOGIC SCALES 2025	MLUMI010000
Country of origin	CHINA



	Class I Div 1&2 Grp ABCD Class II Div 1&2 Grp EFG Class III / Temperature Code T4 IP67 File number: E324236
	II 1G Ex ia IIC T4 IP67 DEMKO 14 ATEX 1354X
	Ex ia IIC T4 Ga IP67 IECEx UL 14.0059X
	0518