



PACKING 	INNER pcs	MASTER pcs
Shrink	10	10



TECHNICAL DATA

Name	BLINK ROAD
Power supply	DRY BATTERIES
Power supply provided	NO
How many batteries are used	1
Battery type	4R25
Batteries provided	(NOT INCLUDED)
Maximum autonomy (h)	900
LED quantity	2
Lighting source	STANDARD LED
Light beam	DIFFUSE
LED lifespan (hours)	30.000
Switch	YES
Functions	BLINK LIGHT / STEADY LIGHT
IP Protection	IP44
Color	RED
Material	PLASTIC - PC
Handbook	https://www.velamp.com/manuali/IL08R_manuale.pdf
Warranty	2 YEARS
Width (mm)	185
Depth (mm)	125
Height (mm)	335
Net weight (Kg)	0.482

DESCRIPTION

Velamp 2-LED red road flasher – with twilight sensor, fixed or flashing mode – high visibility day and night, weatherproof, battery powered HIGH VISIBILITY BOTH DAY AND NIGHT: The flasher is equipped with 2 LEDs with a diffuser designed to ensure maximum visibility in all light conditions, improving road safety in emergency or signalling situations. DUSK SENSOR FOR AUTOMATIC SWITCH-ON: Thanks to the integrated twilight sensor, the device switches on automatically when the light goes down, reducing energy consumption and always ensuring a prompt signal when needed. ADJUSTABLE LIGHTING MODE: You can choose between steady or flashing light, depending on your needs. This versatile option allows you to adapt the flasher's use to different signaling and road safety situations. DURABLE AND DESIGNED FOR OUTDOOR CONDITIONS: Made with a rugged polycarbonate body, it is impact, UV, and weather resistant, ensuring prolonged outdoor use. The IP34 rating makes it ideal for all weather conditions. The product operates with a 6-volt 4R25 or 4LR25 battery – Not included, please purchase separately.

LOGISTICS DATA

Packing type	Shrink
Packed product weight (kg)	0.482
Quantity in inner	10



LOGISTICS DATA

ITF INNER	18003910006659
Quantity in master	10
INTRASTAT Code	85308000
DEEE	0.08



Chiave multifunzione inclusa
Multifunction key included



Funziona con 1 x 4R25 / Works with 1 x 4R25
Non inclusa / Not included

