



PACKING	INNER	MASTER
 / 	 pcs	 pcs
Polybag	12	24



TECHNICAL DATA

Power supply	220V AC
Power supply provided	YES
Type of power supply provided	INTERNAL DRIVER
Lighting source	2835 SMD LED
Light technology	LED SMD
Lighting power (W)	4
Lumen	400
IRC	>80
Light beam	DIFFUSE
Beam angle (°)	360°
Scope (m)	5
Material	PLASTIC - PC
Power cord length (cm)	500
Cable section	H05VV-F 2x0.75mm ²
Cable length (meters)	5
Switch	NO
Insulation class	II
Energy class	F
Lamp included	BULB INCLUDED
Plug	Type C/EF - 2 pin (Europlug/FR-DE Hybrid)
Code eprel	1208116
Link db eprel	http://eprel.ec.europa.eu/qr/1208116
Warranty	2 YEARS
Width (mm)	460
Depth (mm)	37
Height (mm)	37
Net weight (Kg)	0.370

DESCRIPTION

SMD LED: performance and energy saving. Super bright: 400 lumens, 4W of consumption. Cable 5 meters H05VV-F 2x0.75mm². Particularly suitable in the workshop and for the hobby. Comfortable 360 ° hook to hang it anywhere.

LOGISTIC INFORMATION

Packing type	Polybag
Pack length (mm)	40
Pack width (mm)	120
Pack height (mm)	480
Packed product weight (kg)	10.090
Inner width (cm)	53
Inner length (cm)	23
Inner height (cm)	10
Quantity in inner	12
Gross weight inner (kg)	2.520
ITF INNER	18003910923185
Master length (cm)	47
Master width (cm)	53
Master height (cm)	21
Quantity in master	24
Master gross weight (kg)	10.090
ITF MASTER	28003910923182
How many pieces on 80x120 pallet (pz)	504
INTRASTAT Code	85131000
DEEE	0.06

