



10W

6500K  
COLD LIGHT



PACKING	INNER	MASTER
/	pcs	pcs
<b>Colour Box</b>	<b>6</b>	<b>36</b>



## TECHNICAL DATA


Power supply	220V AC
Power supply provided	YES
Type of power supply provided	INTERNAL DRIVER
Lighting source	2835 SMD LED
Lighting power (W)	10
Electricity consumption (W)	10
Lumen	800
IRC	>80
Light beam	DIFFUSE
Beam angle (°)	120°
Detection angle (°)	120°
Detector operation time	10 SEC TO 8 MN
LED lifespan (hours)	25000
Material	ALUMINIUM
Number of on-off cycles	15000
Power cord length (cm)	15
Cable section	H05VV-F 3G1.0mm2
Switch	NO
Accessories included	Cable 15 cm VDE
IP Protection	IP44
Insulation class	I
Energy class	F
Light colour	6500K
Dimmability	NOT DIMMABLE
Lamp included	(INCLUDED)
Energy Label	<a href="https://www.velamp.com/energylabels2021/IS743-5-6500K.jpg">https://www.velamp.com/energylabels2021/IS743-5-6500K.jpg</a>
Code eprel	691867
Link db eprel	<a href="http://eprel.ec.europa.eu/qr/691867">http://eprel.ec.europa.eu/qr/691867</a>
Warranty	2 YEARS
Width (mm)	110
Depth (mm)	41
Height (mm)	158
Net weight (Kg)	0.220
Eprel card	<a href="https://eprel.ec.europa.eu/fiches/lightsources/Fiche_691867_EN.pdf">https://eprel.ec.europa.eu/fiches/lightsources/Fiche_691867_EN.pdf</a>

## DESCRIPTION

Detection Function: Equipped with a PIR motion sensor (passive infrared sensor), this floodlight has powerful infrared human body detection, instant on, convenient, and energy-saving. Detection distance, angle, timing, and brightness can be manually set and adjusted. High Brightness: The use of high-quality, highly efficient SMD 2835 LEDs makes this headlight particularly bright and long-lasting. 800 lumens of light and 10W: It can replace a traditional 100W incandescent bulb, saving over 85% on your electricity bill. IP44 Waterproof: Made of die-cast aluminum and tempered glass, the floodlight is IP44 waterproof, rust-resistant and surface-treated with high-quality electrostatic material, can be widely used in indoor and outdoor lighting projects. Perfect Design: Aluminum body with tempered glass diffuser for excellent light transmission. High-quality aluminum makes the lamp more durable. The nanometer material reflector is safe and durable. Furthermore, the diffusion is 1.4 times higher than traditional LED headlights. Good Heat Dissipation: Ultra-thin design and the use of high self-heating 2835 LEDs ensure the best heat dissipation performance, the headlight can quickly lower the temperature and thus ensure the long life of the headlight and safety in use.

## LOGISTICS DATA

Packing type	Colour Box
Pack length (mm)	50
Pack width (mm)	115
Pack height (mm)	162
Packed product weight (kg)	10.700
Inner width (cm)	34
Inner length (cm)	31
Inner height (cm)	18
Quantity in inner	6
Gross weight inner (kg)	1.700
ITF INNER	18003910107028
Master length (cm)	41
Master width (cm)	34
Master height (cm)	39
Quantity in master	36
Master gross weight (kg)	10.700
ITF MASTER	28003910107025
How many pieces on 80x120 pallet (pz)	720
INTRASTAT Code	94054110
DEEE	0.06
ECOLOGIC SCALES 2025	MLUMI010000
Country of origin	CHINA



**advanced radiator, safe to use**  
25000 hours of service life

