



PACKING	INNER	MASTER
/	pcs	pcs
Colour Box	8	8



TECHNICAL DATA

Power supply	220V AC
Power supply provided	YES
Type of power supply provided	INTERNAL DRIVER
Lighting source	2835 SMD LED
Lighting power (W)	20
Lumen	1600
Light beam	DIFFUSE
Beam angle (°)	100°
Material	ALUMINIUM
Power cord length (cm)	150
Cable section	H05RN-F G1.0mm ²
Switch	NO
IP Protection	IP65
Insulation class	I
Product container (energy class)	G
Plug	Type E / F - 2 pin (EU Hybrid)
Container product (registered form code)	2120A
Energy Label	https://www.velamp.com/energylabels2021/IS750-3.jpg
Code eprel	1094794
Link db eprel	http://eprel.ec.europa.eu/qr/1094794
Warranty	2 YEARS
Width (mm)	170
Depth (mm)	163
Height (mm)	230
Net weight (Kg)	0.946

DESCRIPTION

POWER: the 20W / 1600 lumen energy saving LED spotlight illuminates the construction site with a cold white light (6500K) and optimizes working conditions, even outdoors (IP65). Average lifespan of 25,000 hours, energy class A + with low consumption. **practically EVERYWHERE:** the portable lamp is useful for work outside, on the construction site, in the workshop, in the garden, on the camping site or in the garage. The headlight is also waterproof and is suitable for both indoor and outdoor use. **EASY TO USE:** Adjustable metal bracket with padded handle to easily move the work lamp on the construction site. Wide base for better stability. **SIMPLE:** the construction site lamp is equipped with a 1.5 m long neoprene power cable (H05RN-F 3G1.0MM2), which can be connected to any European socket (Schuko socket). **space SAVER:** the portable spotlight is small, it can be stored and transported comfortably.

Packing type	Colour Box
Pack length (mm)	105
Pack width (mm)	175
Pack height (mm)	235
Inner length (cm)	36
Inner height (cm)	44
Quantity in inner	8
Gross weight inner (kg)	9.860
ITF INNER	18003910105017
Quantity in master	8
How many pieces on 80x120 pallet (pz)	216
INTRASTAT Code	94054110
DEEE	0.11



