



PACKING	INNER	MASTER
/	pcs	pcs
Colour Box	8	16



TECHNICAL DATA


Power supply	220V AC
Power supply provided	YES
Type of power supply provided	INTERNAL DRIVER
Lighting source	2835 SMD LED
Lighting power (W)	50
Electricity consumption (W)	50
Lumen	4250
IRC	>80
Light beam	DIFFUSE
Beam angle (°)	120°
LED lifespan (hours)	25.000
Material	ALUMINIUM
Number of on-off cycles	15000
Power cord length (cm)	15
Cable section	H05VV-F 3G1.0mm2
Switch	NO
Accessories included	Cable 15 cm VDE
IP Protection	IP65
Insulation class	I
Energy class	F
Light colour	4000K
Dimmability	NOT DIMMABLE
Lamp included	(INCLUDED)
Energy Label	https://www.velamp.com/energylabels2021/IS760-5-4000K.jpg
Code eprel	691998
Link db eprel	http://eprel.ec.europa.eu/qr/691998
Warranty	2 YEARS
Width (mm)	225
Depth (mm)	50
Height (mm)	130
Net weight (Kg)	0.859
Eprel card	https://eprel.ec.europa.eu/fiches/lightsources/Fiche_691998_EN.pdf

DESCRIPTION

High Brightness: The use of high-quality, highly efficient SMD 2835 LEDs makes this headlight particularly bright and long-lasting. 4000 lumens and 50W: It can replace a traditional 400W incandescent bulb, saving over 85% on your electricity bill. **IP65 Waterproof:** Made of die-cast aluminum and tempered glass, the floodlight is IP65 waterproof, rust-resistant and surface treated with high-quality electrostatic material, can be widely used in indoor and outdoor lighting projects. **Perfect Design:** Aluminum body with tempered glass diffuser for excellent light transmission. High-quality aluminum makes the lamp more durable. The nanometer material reflector is safe and durable. Furthermore, the diffusion is 1.4 times higher than traditional LED headlights. **Good Heat Dissipation:** Ultra-thin design and the use of high self-heating 2835 LEDs ensure the best heat dissipation performance, the headlight can quickly lower the temperature and thus ensure the long life of the headlight and safety in use. **Versatile:** With a 360-degree adjustable angle, it can be installed on the ceiling, wall, or floor. After installation, the projection surface can be adjusted to any angle. Suitable for outdoor use such as gardens, courtyards, plazas, and piers.

LOGISTICS DATA

Packing type	Colour Box
Pack length (mm)	60
Pack width (mm)	230
Pack height (mm)	150
Packed product weight (kg)	14.720
Inner width (cm)	48
Inner length (cm)	25
Inner height (cm)	30
Quantity in inner	8
Gross weight inner (kg)	7.360
ITF INNER	18003910106946
Master length (cm)	26
Master width (cm)	48
Master height (cm)	32
Quantity in master	16
Master gross weight (kg)	14.720
ITF MASTER	28003910106943
How many pieces on 80x120 pallet (pz)	480
INTRASTAT Code	94054110
DEEE	0.11
ECOLOGIC SCALES 2025	MLUMI030000
Country of origin	CHINA



advanced radiator, safe to use
25000 hours of service life

