



PACKING ☐ / ☑	INNER ☐ pcs	MASTER ☐ pcs
Colour Box	2	4



TECHNICAL DATA


Power supply	220V AC
Power supply provided	YES
Type of power supply provided	INTERNAL DRIVER
Lighting source	2835 SMD LED
Lighting power (W)	150
Electricity consumption (W)	150
Lumen	13000
IRC	>80
Light beam	DIFFUSE
Beam angle (°)	120°
LED lifespan (hours)	25.000
Material	ALUMINIUM
Power cord length (cm)	30
Cable section	H05VV-F 3G1.0mm2
Switch	NO
Accessories included	Cable 15 cm VDE
IP Protection	IP65
Insulation class	I
Energy class	F
Light colour	6500K
Dimmability	NOT DIMMABLE
Lamp included	(INCLUDED)
Energy Label	https://www.velamp.com/energylabels2021/IS783.jpg
Code eprel	674360
Link db eprel	http://eprel.ec.europa.eu/qr/674360
Warranty	2 YEARS
Width (mm)	337
Depth (mm)	281
Height (mm)	53
Net weight (Kg)	3.574
Eprel card	https://eprel.ec.europa.eu/fiches/lightsources/Fiche_674360_EN.pdf

DESCRIPTION

Ultra High Brightness: The use of high-quality SMD LEDs ensures high luminous efficiency (12,500 real lumens), long life, excellent heat dissipation performance; Lifespan: 25,000 hours; Driver: to give it a more compact size than traditional spotlights. Waterproof and durable: IP65 waterproof, suitable for both indoor and outdoor use; the use of ultra-resistant materials such as tempered glass and high-quality die-cast aluminum makes the lamp particularly resistant to shocks and atmospheric agents. Ideal for illuminating a warehouse, garage, outdoor area like the garden or driveway; wherever you need it; the 120° diffused beam makes it a perfect lighting tool even for walls and facades. Ultra-low energy consumption: The outdoor LED floodlight saves you up to 80% electricity compared to ordinary lights, directly reducing your electricity bills. Cold light 6500K; non-dimmable; class I; special waterproof connector that will allow you to connect the spotlight easily, quickly and durably.

LOGISTICS DATA

Packing type	Colour Box
Pack length (mm)	290
Pack width (mm)	355
Pack height (mm)	80
Packed product weight (kg)	8.000
Inner width (cm)	17
Quantity in inner	2
ITF INNER	18003910104584
Master length (cm)	37
Master width (cm)	17
Master height (cm)	31
Quantity in master	4
Master gross weight (kg)	8.000
How many pieces on 80x120 pallet (pz)	288
INTRASTAT Code	94054110
DEEE	0.42
ECOLOGIC SCALES 2025	MLUMI030000
Country of origin	CHINA



advanced radiator, safe to use
25000 hours of service life

