



| PACKING           | INNER    | MASTER    |
|-------------------|----------|-----------|
| /                 | pcs      | pcs       |
| <b>Colour Box</b> | <b>8</b> | <b>32</b> |



## TECHNICAL DATA

|                                   |                                                                                                                                                         |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply                      | 220V AC                                                                                                                                                 |
| Type of power supply provided     | INTERNAL DRIVER                                                                                                                                         |
| Lighting source                   | SMD LED                                                                                                                                                 |
| Lighting power (W)                | 24                                                                                                                                                      |
| Electricity consumption (W)       | 24                                                                                                                                                      |
| Incandescent equivalent power (W) | 150                                                                                                                                                     |
| Lumen                             | 2500                                                                                                                                                    |
| IRC                               | >80                                                                                                                                                     |
| Light beam                        | DIFFUSE                                                                                                                                                 |
| Beam angle (°)                    | 240°                                                                                                                                                    |
| LED lifespan (hours)              | 20.000                                                                                                                                                  |
| Material                          | PLASTIC + ALUMINIUM                                                                                                                                     |
| Number of on-off cycles           | >10000                                                                                                                                                  |
| Bulb shape                        | G125                                                                                                                                                    |
| Attachment                        | E27 LAMP                                                                                                                                                |
| Energy class                      | F                                                                                                                                                       |
| Light colour                      | 3000K                                                                                                                                                   |
| Dimmability                       | NOT DIMMABLE                                                                                                                                            |
| Lamp included                     | (INCLUDED)                                                                                                                                              |
| Energy Label                      | <a href="https://www.velamp.com/energylabels2021/LB224S-30K.jpg">https://www.velamp.com/energylabels2021/LB224S-30K.jpg</a>                             |
| Code eprel                        | 1550267                                                                                                                                                 |
| Link db eprel                     | <a href="http://eprel.ec.europa.eu/qr/1550267">http://eprel.ec.europa.eu/qr/1550267</a>                                                                 |
| Warranty                          | 2 YEARS                                                                                                                                                 |
| Width (mm)                        | 125                                                                                                                                                     |
| Depth (mm)                        | 125                                                                                                                                                     |
| Height (mm)                       | 173                                                                                                                                                     |
| Net weight (Kg)                   | 0.137                                                                                                                                                   |
| Handbook                          | <a href="https://www.velamp.com/manuali/ISTRUZIONI_LAMPADINE_ALL_LANGUAGE.pdf">https://www.velamp.com/manuali/ISTRUZIONI_LAMPADINE_ALL_LANGUAGE.pdf</a> |
| Eprel card                        | <a href="https://eprel.ec.europa.eu/fiches/lightsources/Fiche_1550267_EN.pdf">https://eprel.ec.europa.eu/fiches/lightsources/Fiche_1550267_EN.pdf</a>   |

## DESCRIPTION

With a lifespan of 20,000 hours (well beyond the standards you will find on the market), the bulb can last over 15 years (with 3 hours of daily use). It produces 2500 lumens of instant brightness, without having to wait for the bulb to warm up. The opalized diffuser makes the light uniform, glare-free, and well-diffused (240° beam angle). With a color temperature of 3000 Kelvin, the bulb provides warm white light, creating a comfortable atmosphere in any room. Perfect for any room in the home, such as the bedroom, living room, bathroom, and office. It consumes 24 watts of energy and costs less than 4 euros a year to operate, offering significant energy savings compared to an incandescent light bulb. It's equivalent to a traditional 150W light bulb. The high color rendering index (CRI > 80) offers natural, vivid colors. This bulb is not dimmable and not compatible with dimmer switches.

## LOGISTICS DATA

|                                       |                |
|---------------------------------------|----------------|
| Packing type                          | Colour Box     |
| Pack length (mm)                      | 130            |
| Pack width (mm)                       | 130            |
| Pack height (mm)                      | 180            |
| Packed product weight (kg)            | 10.200         |
| Inner width (cm)                      | 55             |
| Inner length (cm)                     | 27             |
| Inner height (cm)                     | 21             |
| Quantity in inner                     | 8              |
| Gross weight inner (kg)               | 2.200          |
| ITF INNER                             | 18003910112640 |
| Master length (cm)                    | 55             |
| Master width (cm)                     | 55             |
| Master height (cm)                    | 43             |
| Quantity in master                    | 32             |
| Master gross weight (kg)              | 10.200         |
| ITF MASTER                            | 28003910112647 |
| How many pieces on 80x120 pallet (pz) | 240            |
| INTRASTAT Code                        | 85395200       |
| ECOLOGIC SCALES 2025                  | N/A            |
| Country of origin                     | CHINA          |

