



PACKING	INNER	MASTER
/	pcs	pcs
<b>Colour Box</b>	<b>10</b>	<b>100</b>



## TECHNICAL DATA

Power supply	220V AC
Type of power supply provided	INTERNAL DRIVER
Lighting source	SMD LED
Lighting power (W)	8
Electricity consumption (W)	8
Incandescent equivalent power (W)	60
Lumen	806
IRC	>80
Light beam	DIFFUSE
Beam angle (°)	180°
LED lifespan (hours)	20.000
Material	PLASTIC + ALUMINIUM
Number of on-off cycles	>10000
Bulb shape	P45
Attachment	E27 LAMP
Energy class	F
Light colour	3000K
Dimmability	NOT DIMMABLE
Lamp included	(INCLUDED)
Energy Label	<a href="https://www.velamp.com/energylabels2021/LB4087S-30K.jpg">https://www.velamp.com/energylabels2021/LB4087S-30K.jpg</a>
Code eprel	1550425
Link db eprel	<a href="http://eprel.ec.europa.eu/qr/1550425">http://eprel.ec.europa.eu/qr/1550425</a>
Warranty	2 YEARS
Width (mm)	45
Depth (mm)	45
Height (mm)	80
Net weight (Kg)	0.025
Handbook	<a href="https://www.velamp.com/manuali/ISTRUZIONI_LAMPADINE_ALL_LANGUAGE.pdf">https://www.velamp.com/manuali/ISTRUZIONI_LAMPADINE_ALL_LANGUAGE.pdf</a>
Epel card	<a href="https://eprel.ec.europa.eu/fiches/lightsources/Fiche_1550425_EN.pdf">https://eprel.ec.europa.eu/fiches/lightsources/Fiche_1550425_EN.pdf</a>

## DESCRIPTION

With a lifespan of 20,000 hours (well beyond the standards you will find on the market), the bulb can last over 15 years (with 3 hours of daily use). It produces 806 lumens of instant brightness, without having to wait for the bulb to warm up. The opalized diffuser makes the light uniform, glare-free, and well-diffused (180° beam angle). With a color temperature of 3000 Kelvin, the bulb provides warm white light, creating a comfortable atmosphere in any room. Perfect for any room in the home, such as the bedroom, living room, bathroom, and office. Ideal for bedside lamps, range hood lamps, study lights, chandeliers, and wall lamps. It consumes 8 watts of energy and costs less than €2.50 per year to operate, offering significant energy savings compared to an incandescent light bulb. It's equivalent to a traditional 60W light bulb. The high color rendering index (CRI > 80) offers natural, vivid colors. This bulb is not dimmable and not compatible with dimmer switches.

## LOGISTICS DATA

Packing type	Colour Box
Pack length (mm)	45
Pack width (mm)	45
Pack height (mm)	80
Packed product weight (kg)	3.800
Inner width (cm)	26
Inner length (cm)	24
Inner height (cm)	9
Quantity in inner	10
Gross weight inner (kg)	0.300
ITF INNER	18003910112831
Master length (cm)	53
Master width (cm)	26
Master height (cm)	20
Quantity in master	100
Master gross weight (kg)	3.800
ITF MASTER	28003910112838
How many pieces on 80x120 pallet (pz)	3000
INTRASTAT Code	85395200
DEEE	0.1
ECOLOGIC SCALES 2025	N/A
Country of origin	CHINA

