



PACKING 	INNER  pcs	MASTER  pcs
Polybag	10	50



TECHNICAL DATA

Power supply	220V AC
Power cord length (cm)	200
Cable section	H03VVH2-F 2x0.75mm5
Switch	YES
Absorption (A)	2.5
Plug	Type C/EF - 2 pin (Europlug/FR-DE Hybrid WITHOUT EARTH)
IP Protection	IP20
Insulation class	II
Color	WHITE
Country of origin	CHINA
Material	PLASTIC - OTHER
Width (mm)	50
Depth (mm)	50
Height (mm)	170
Net weight (Kg)	0.100

DESCRIPTION

High strength plastic sheathed cable: 2 meters, H03VVH2-F 2x0.75 plastic sheathed cable. Power supply: The flat Euro plug (230V/2.5A) and 30mm sleeve ensure a simple and effective power connection. Equipped with a single-pole intermediate switch. Reliability and durability: The cable jacket is made of flame-retardant PVC plastic. The core is made of high-quality copper. The cables are suitable for indoor use. Cable length between plug and switch: approximately 120 cm. Cable length between switch and terminals: approximately 80 cm. Ideal for replacing a faulty cable, creating your own lamp, powering at 220V~compatible objects...

LOGISTICS DATA

Packing type	Polybag
Pack length (mm)	50
Pack width (mm)	50
Pack height (mm)	170
Packed product weight (kg)	0.100
Inner width (cm)	24
Inner length (cm)	22
Inner height (cm)	10
Quantity in inner	10
Gross weight inner (kg)	1.100
ITF INNER	18003910115498

LOGISTICS DATA

Master length (cm)	53
Master width (cm)	24
Master height (cm)	17
Quantity in master	50
Master gross weight (kg)	5.900
ITF MASTER	28003910115495
How many pieces on 80x120 pallet (pz)	2000
INTRASTAT Code	85139000
DEEE	0.02
ECOLOGIC SCALES 2025	MCABC010000
Country of origin	CHINA