

DATA SHEET

Single-pole terminals 2.5mm², 10-pole strip



PACKING 	INNER 	MASTER
Shrink	100	800



TECHNICAL DATA

Rated voltage (V)	450
Installation height (m)	0
Absorption (A)	24
Maximum diameter for cable insertion (mm ²)	2.5
Electric current intensity (A)	24
Country of origin	CHINA
Material	PLASTIC - PC
Warranty	2 YEARS
Width (mm)	100
Depth (mm)	15
Height (mm)	20
Net weight (Kg)	0.013

DESCRIPTION

Easy pole detachment, leaves no residue and does not sting your fingers. Clamps in sticks of 10 pieces each. Transparent shell for excellent visibility of the connection. Polycarbonate shell, brass insert, zinc-plated steel screw. Material: PC polycarbonate, good flexibility, transparency, extensibility, radiation resistance. Maximum operating temperature: 85°C. Voltage: 250-450V. With IMQ quality and safety mark.

LOGISTICS DATA

Packing type	Shrink
Pack length (mm)	30
Pack width (mm)	100
Pack height (mm)	70
Packed product weight (kg)	0.017
Inner width (cm)	24
Inner length (cm)	15
Inner height (cm)	15
Quantity in inner	100
Gross weight inner (kg)	1.700
ITF INNER	18003910113142
Master length (cm)	32
Master width (cm)	24
Master height (cm)	32
Quantity in master	800
Master gross weight (kg)	14.000
ITF MASTER	28003910113149

LOGISTICS DATA

How many pieces on 80x120 pallet (pz)	24000
INTRASTAT Code	85369010
ECOLOGIC SCALES 2025	MBJED010000
Country of origin	CHINA

