



PACKING 	INNER  pcs	MASTER  pcs
<b>Shrink</b>	<b>100</b>	<b>500</b>



## TECHNICAL DATA

Rated voltage (V)	450
Installation height (m)	0
Absorption (A)	32
Maximum diameter for cable insertion (mm <sup>2</sup> )	4
Electric current intensity (A)	32
Country of origin	CHINA
Material	PLASTIC - PC
Warranty	2 YEARS
Width (mm)	115
Depth (mm)	20
Height (mm)	25
Net weight (Kg)	0.020

## DESCRIPTION

Easy pole detachment, leaves no residue and does not sting your fingers. Clamps in sticks of 10 pieces each. Transparent shell for excellent visibility of the connection. Polycarbonate shell, brass insert, zinc-plated steel screw. Material: PC polycarbonate, good flexibility, transparency, extensibility, radiation resistance. Maximum operating temperature: 85°C. Voltage: 250-450V. With IMQ quality and safety mark.

## LOGISTICS DATA

Packing type	Shrink
Pack length (mm)	30
Pack width (mm)	120
Pack height (mm)	125
Packed product weight (kg)	0.023
Inner width (cm)	31
Inner length (cm)	17
Inner height (cm)	17
Quantity in inner	100
Gross weight inner (kg)	2.300
ITF INNER	18003910113159
Master length (cm)	40
Master width (cm)	31
Master height (cm)	19
Quantity in master	500
Master gross weight (kg)	11.900
ITF MASTER	28003910113156

## LOGISTICS DATA

How many pieces on 80x120 pallet (pz)	12500
INTRASTAT Code	85369010
ECOLOGIC SCALES 2025	MBJED010000
Country of origin	CHINA

