




PACKING 	INNER  pcs	MASTER  pcs
Shrink	50	300



TECHNICAL DATA

Rated voltage (V)	500
Installation height (m)	0
Absorption (A)	57
Maximum diameter for cable insertion (mm ²)	10
Electric current intensity (A)	57
Country of origin	CHINA
Material	PLASTIC - PC
Warranty	2 YEARS
Width (mm)	165
Depth (mm)	30
Height (mm)	30
Net weight (Kg)	0.060

DESCRIPTION

Easy pole detachment, leaves no residue and does not sting your fingers. Clamps in sticks of 10 pieces each. Transparent shell for excellent visibility of the connection. Polycarbonate shell, brass insert, zinc-plated steel screw. Material: PC polycarbonate, good flexibility, transparency, extensibility, radiation resistance. Maximum operating temperature: 85°C. Voltage: 250-450V. With IMQ quality and safety mark.

LOGISTICS DATA

Packing type	Shrink
Pack length (mm)	40
Pack width (mm)	170
Pack height (mm)	115
Packed product weight (kg)	0.064
Inner width (cm)	38
Inner length (cm)	17
Inner height (cm)	23
Quantity in inner	50
Gross weight inner (kg)	3.200
ITF INNER	18003910113173
Master length (cm)	38
Master width (cm)	38
Master height (cm)	25
Quantity in master	300
Master gross weight (kg)	20.000
ITF MASTER	28003910113170

LOGISTICS DATA

How many pieces on 80x120 pallet (pz)	7200
INTRASTAT Code	85369010
ECOLOGIC SCALES 2025	MBJED010000
Country of origin	CHINA

