



PACKING	INNER	MASTER
	 pcs	 pcs
Polybag	10	50



TECHNICAL DATA

Name	MG8060C
Power supply	450V AC
Power supply provided	NO
Attachment	M8
Power cord length (cm)	15
Switch	NO
Capacity (μ F)	6
Color	WHITE
Country of origin	CHINA
Material	PLASTIC
Warranty	2 YEARS
Width (mm)	30
Depth (mm)	30
Height (mm)	57
Net weight (Kg)	0.062

DESCRIPTION

Capacitance: 6 μ F. Voltage: 450V~. External dimensions (diameter x height): 30*57mm. Electrical connection via 15cm cable. Mechanical fastening via threaded rod and M8 nut. Tolerance 5%. Lifespan: 3000 hours. Operating temperature -40°C.~+70°C. The white round capacitor is designed for continuous operation. This type of capacitor is primarily used in single-phase motors, but can also be used in switching circuits, damping, and general applications.

LOGISTICS DATA

Packing type	Polybag
Pack length (mm)	30
Pack width (mm)	30
Pack height (mm)	80
Packed product weight (kg)	0.062
Inner width (cm)	23
Inner length (cm)	21
Inner height (cm)	6
Quantity in inner	10
Gross weight inner (kg)	0.600
ITF INNER	18003910115863
Master length (cm)	25
Master width (cm)	23

LOGISTICS DATA

Master height (cm)	23
Quantity in master	50
Master gross weight (kg)	3.500
ITF MASTER	28003910115860
How many pieces on 80x120 pallet (pz)	3750
INTRASTAT Code	85322500
ECOLOGIC SCALES 2025	N/A
Country of origin	CHINA



TECNID **START CAPACITOR WITH 15CM CABLE**
 Condensatore di spunto con cavo 15 cm
 Condensateur de démarrage avec câble de 15 cm
 Kondensator starten mit 15 cm Kabel








