



PACKING 	INNER  pcs	MASTER  pcs
Blister	6	24



TECHNICAL DATA

Power supply	220V AC
Detection angle (°)	180°
Sensing distance	max 12m
Detector operation time	8 SEC TO 7 MIN
Installation height (m)	3,5
Operating temperature (°C)	-20°C / +40°C
Maximum load	1000W
IP Protection	IP44
Insulation class	II
Country of origin	CHINA
Material	PLASTIC - ABS
Warranty	2 YEARS
Width (mm)	86
Depth (mm)	100
Height (mm)	80
Net weight (Kg)	0.127

DESCRIPTION

Infrared motion detector (PIR) for the automation of 220V lighting systems. The motion detector is designed to detect movement within the detection area and thus automatically turn on 220V lighting systems. In addition to being convenient to use, it will offer you significant energy savings as the connected lights will only activate in the dark and when motion is detected; maximum load: 1000W. Adjustment: - of the duration of the connected system's activation - of the sensitivity of detection in the dark: it will be possible to adjust the level of darkness required to activate the connected system. Comfort and savings guaranteed.

LOGISTICS DATA

Packing type	Blister
Pack length (mm)	90
Pack width (mm)	200
Pack height (mm)	160
Packed product weight (kg)	0.180
Inner width (cm)	53
Inner length (cm)	28
Inner height (cm)	16
Quantity in inner	6
Gross weight inner (kg)	1.080
ITF INNER	18003910104485

LOGISTICS DATA

Master length (cm)	30
Master width (cm)	53
Master height (cm)	35
Quantity in master	24
Master gross weight (kg)	4.700
ITF MASTER	28003910104482
How many pieces on 80x120 pallet (pz)	576
INTRASTAT Code	85365080
DEEE	0.02
ECOLOGIC SCALES 2025	MBJED010000
Country of origin	CHINA

