



PACKING	INNER	MASTER
	pcs	pcs
Blister	6	36



TECHNICAL DATA

Power supply	220V AC
Power supply provided	NO
Detection angle (°)	180°
Sensing distance	max 12m
Detector operation time	10 SEC TO 15 MIN
Switch	NO
Operating temperature (°C)	-20°C / +40°C
Maximum load	1200W
IP Protection	IP65
Insulation class	II
Country of origin	CHINA
Material	PLASTIC - PC
Warranty	2 YEARS
Width (mm)	80
Depth (mm)	60
Height (mm)	100
Net weight (Kg)	0.200

DESCRIPTION

Infrared motion detector (PIR) for automating 220V lighting systems; ideal for controlling lights as well as air conditioning, fans, and anything else that works with a 220V switch; precise recognition of people, animals, etc. within range. The motion detector is designed to detect movement within the detection area and thus automatically turn on the connected systems. In addition to being convenient to use, it will offer you significant energy savings as the connected lights will only activate in the dark and when motion is detected. Maximum load: 1200W. Indoor or outdoor use (IP65 waterproof). Tilttable head. Adjustment: - the duration of the connected system's activation (from 10 seconds to 15 minutes) - the sensitivity of detection in darkness: you can adjust the level of darkness required to activate the connected system; you can thus decide whether to trigger the relay during the day or in the middle of the night. The detection range of the motion sensor is approximately 12m and 180°. Simple and easy assembly; screws provided.

LOGISTICS DATA

Packing type	Blister
Pack length (mm)	155
Pack width (mm)	200
Pack height (mm)	60
Packed product weight (kg)	0.224
Inner width (cm)	34
Inner length (cm)	31
Inner height (cm)	16

LOGISTICS DATA

Quantity in inner	6
Gross weight inner (kg)	1.500
ITF INNER	18003910112503
Master length (cm)	69
Master width (cm)	34
Master height (cm)	35
Quantity in master	36
Master gross weight (kg)	9.800
ITF MASTER	28003910112500
How many pieces on 80x120 pallet (pz)	432
INTRASTAT Code	85365080
DEEE	0.02
ECOLOGIC SCALES 2025	MBJED010000
Country of origin	CHINA

