



**250V**

PRISE VOLANTE  
STANDARD  
FRANÇAISE 16A



PACKING 	INNER pcs	MASTER pcs
<b>Bulk</b>	<b>10</b>	<b>100</b>

Pays compatibles:



## TECHNICAL DATA

Name	PLUG-FR-16F
Power supply	220V AC
Power supply provided	NO
Switch	NO
Absorption (A)	16A
Main socket	French type 2P+T
Number of sockets	1
IP Protection	IP20
Insulation class	I
Color	WHITE
Material	PLASTIC - PC
NF	YES
Warranty	2 YEARS
Width (mm)	45
Depth (mm)	45
Height (mm)	60
Net weight (Kg)	0.041

## DESCRIPTION


Standard French 16A flying socket. For French plugs. Made of high-quality, shock-proof material: The protective contact connector is made of polycarbonate, which is wear-resistant and drop-resistant, durable and guaranteed for long-term use. Suitable for connecting extension cords or installing and repairing damaged connectors. Supports up to 250V (16A). Complies with NF (Normes Françaises) regulations. Designed for H05VV-F3G1.0mm<sup>2</sup> and H05VV-F3G1.5mm<sup>2</sup> cables.

## LOGISTICS DATA

Packing type	Bulk
Pack length (mm)	45
Pack width (mm)	45
Pack height (mm)	60
Packed product weight (kg)	0.041
Inner width (cm)	24
Inner length (cm)	23
Inner height (cm)	5
Quantity in inner	10
Gross weight inner (kg)	0.400
ITF INNER	18003910116914

## LOGISTICS DATA


Master length (cm)	28
Master width (cm)	24
Master height (cm)	26
Quantity in master	100
Master gross weight (kg)	4.500
ITF MASTER	28003910116911
How many pieces on 80x120 pallet (pz)	6000
INTRASTAT Code	85366190
DEEE	0.03



**E: CONDUCTEUR DE PROTECTION**  
Assure la sécurité par la mise à la terre  
(vert/jaune)

**L: CONDUCTEUR EXTÉRIEUR**  
Conduit le courant de service  
(marron)

**N: CONDUCTEUR NEUTRE**  
Conducteur de retour dans le circuit  
de courant alternatif  
(bleu)



CONÇU POUR LES CÂBLES H05VV-F3G1.0 mm<sup>2</sup>  
ET H05VV-F3G1.5mm<sup>2</sup>

