



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	1	1



TECHNICAL DATA

Name	PR162C
Power supply	220V AC
Power supply provided	YES
Type of power supply provided	POWER CABLE
Electricity consumption (W)	900
Power cord length (cm)	140
Cable section	H05VV-F 3Gx0.75
Switch	YES
Functions	HOT + OSCILLATION
Absorption (A)	3.75
Plug	Type E / F - 2 pin (EU Hybrid)
Power adjustment (W)	450W/900W
Timer	NO
Fuse required	YES
Auto reset thermostat	NO
Heating area (m ²)	10
Operating temperature (°C)	-15°C + 25°C
IP Protection	IPX0
Insulation class	I
Color	DARK GREY
Country of origin	CHINA
Material	PLASTIC - OTHER
Warranty	2 YEARS
Width (mm)	700
Depth (mm)	230
Height (mm)	80
Net weight (Kg)	1.738

DESCRIPTION

OSCILLATING CARBON HEATER | Managing the temperature in your home and office is essential to your well-being: treat yourself to the luxury of fast and effective heating with the Velamp electric carbon heater, making any room you choose to install it in a pleasant environment (30m² range) with the guarantee of low energy consumption. **CARBON TECHNOLOGY** | For heating small spaces in your home or office, electric carbon heaters are the ideal solution: electric carbon heaters radiate heat through radiation, a function designed to heat surfaces rather than the air, ensuring immediate heating. **CONVENIENT AND PORTABLE** | Whether it's the bedroom, living room, or office, the Velamp carbon heater goes everywhere with you thanks to its integrated handle, ensuring uniform, energy-efficient heat: equipped with horizontal oscillation, use the manual controls on this carbon heater to heat any surface you want to use it on without leaving colder areas. **COMPACT AND SAFE** | The dimensions of this low-consumption electric oscillating charcoal stove (LxWxH) are: 30cm x 30cm x 72cm. Depending on the two power levels, the electric stove has a power output of 450/900W and can handle 220-240V. Furthermore, it is a safe charcoal stove, thanks to the anti-tip protection. Equipped with a 140cm cable with a CEE 7/7 (Schuko) socket; highly resistant thermoplastic structure; IPX0; operating temperature: -15°C / +25°C.

LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	310
Pack width (mm)	710
Pack height (mm)	160
Packed product weight (kg)	2.285
Quantity in inner	1
Quantity in master	1
How many pieces on 80x120 pallet (pz)	40
INTRASTAT Code	85162991
DEEE	0.21
ECOLOGIC SCALES 2025	MCHAE010000
Country of origin	CHINA



INTERRUTTORE DI SICUREZZA



Si spegne automaticamente se capovolto
Automatically shuts off if tipped

