



PACKING 	INNER pcs	MASTER pcs
Blister	6	36



TECHNICAL DATA

Power supply	220V AC
Power supply provided	YES
Type of power supply provided	INTERNAL DRIVER
How many batteries are used	1
Stack technology	LI-PO
Rated voltage (V)	3,7
Battery capacity (mAh)	300
Batteries provided	(INCLUDED)
Battery/battery weight (kg)	0.006
Maximum autonomy (h)	5
LED quantity	6
Lighting source	SMD LED
Lighting power (W)	1
Lumen	40
Light colour	4000K
Light beam	DIFFUSE + FOCUS
Plug	Type C/EF - 2 pin (Europlug/FR-DE Hybrid)
Insulation class	II
Country of origin	CHINA
Material	PLASTIC - PC
Warranty	2 YEARS
Width (mm)	59
Depth (mm)	75
Height (mm)	112
Net weight (Kg)	0.095

DESCRIPTION

Multifunction: spot light, automatic emergency light and flashlight. In the event of a power outage, the upper flashlight turns on thanks to the automatic switch-on function; you can then detach the lamp from its base and use it as a convenient flashlight. With motion detector: the main (central) light turns on only in the dark and when it detects motion. With induction charging base: convenient, technological and simple. 10A plug compatible with all sockets (10A-16A-schuko).

LOGISTICS DATA

Packing type	Blister
Pack length (mm)	70
Pack width (mm)	160

LOGISTICS DATA

Pack height (mm)	210
Packed product weight (kg)	0.139
Inner width (cm)	72
Inner length (cm)	35
Inner height (cm)	19
Quantity in inner	6
Gross weight inner (kg)	0.830
ITF INNER	18003910101699
Master length (cm)	48
Master width (cm)	72
Master height (cm)	40
Quantity in master	36
Master gross weight (kg)	6.680
ITF MASTER	28003910101696
How many pieces on 80x120 pallet (pz)	432
INTRASTAT Code	85131000
DEEE	0.02
ECOLOGIC SCALES 2025	MLUMI010000
Country of origin	CHINA

