



PACKING 	INNER pcs	MASTER pcs
Blister	6	36



TECHNICAL DATA	
Power supply	220V AC
Power supply provided	YES
Type of power supply provided	INTERNAL DRIVER
How many batteries are used	1
Battery type	OTHER
Stack technology	LI-PO
Rated voltage (V)	3,7
Battery capacity (mAh)	300
Batteries provided	(INCLUDED)
Power battery (Wh)	1.11
Battery class	9
Battery/battery weight (kg)	0.006
Maximum autonomy (h)	5
LED quantity	6
Lighting source	SMD LED
Lighting power (W)	1
Lumen	40
Light colour	4000K
Light beam	DIFFUSE + FOCUS
Plug	Type C/EF - 2 pin (Europlug/FR-DE Hybrid)
Insulation class	II
Country of origin	CHINA
Material	PLASTIC - PC
Standards	UN3481
Warranty	2 YEARS
Width (mm)	59
Depth (mm)	112
Height (mm)	75
Net weight (Kg)	0.095

DESCRIPTION

Multifunction: spot light, automatic emergency light and flashlight. In the event of a power outage, the upper flashlight turns on thanks to the automatic switch-on function; you can then detach the lamp from its base and use it as a convenient flashlight. With motion detector: the main (central) light turns on only in the dark and when it detects motion. With induction charging base: convenient, technological and simple. 10A plug compatible with all sockets (10A-16A-schuko).

LOGISTICS DATA

Packing type	Blister
Pack length (mm)	80
Pack width (mm)	150
Pack height (mm)	200
Packed product weight (kg)	0.143
Inner width (cm)	45
Inner length (cm)	22
Inner height (cm)	18
Quantity in inner	6
Gross weight inner (kg)	0.860
ITF INNER	18003910904641
Master length (cm)	38
Master width (cm)	45
Master height (cm)	56
Quantity in master	36
Master gross weight (kg)	5.100
ITF MASTER	28003910904648
INTRASTAT Code	85131000
DEEE	0.02
ECOLOGIC SCALES 2025	MLUMI010000
Country of origin	CHINA

