



PACKING	INNER	MASTER
	pcs	pcs
Colour box	6	48



TECHNICAL DATA

Name	SH008
Power supply	220V AC
Switch	YES
Plug	Type Italy tripolar 16A
Main socket	Type Italy tripolar 16A
Number of sockets	1
Timer	YES
Maximum load	3680W
Insulation class	II
Color	WHITE
Children protection	YES
Country of origin	CHINA
Material	PLASTIC - PC
Warranty	2 YEARS
Width (mm)	125
Depth (mm)	75
Height (mm)	70
Net weight (Kg)	0.160

DESCRIPTION

The VELAMP daily mechanical programmer is simple to use: it will allow you to control the switching on and off of any connected household appliance (230V~50Hz – 3680W max.) such as a coffee machine, fan, penguin, lamp, washing machine, bathroom heater, printer, etc. Programming is simple, and you can create one or more schedules over a 24-hour period. Each segment represents a 15-minute block of time in a 24-hour day (a day). The schedule(s) will repeat every day until changed. It can also be disabled when you don't want to use the scheduler function. Technical features: Maximum load 16A, max. 3680W. For indoor use only. Keep away from water. Child safety lock: prevents foreign objects from entering the live socket. Energy Saving: Plug-in timer outlets are a convenient way to save time and energy on your appliances and devices. Your outlets and devices don't have to be on 24/7. With intelligent scheduling, the Velamp timer can help you save money on your electric bills by programming when your outlets turn on and off. Great for Christmas tree/outdoor lights. This simple, affordable product is easy to use, just set it once and forget it - only reset when you want to change the on/off times.

LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	85
Pack width (mm)	85
Pack height (mm)	125
Packed product weight (kg)	0.180
Inner width (cm)	33

LOGISTICS DATA

Inner length (cm)	26
Inner height (cm)	14
Quantity in inner	6
Gross weight inner (kg)	1.200
ITF INNER	18003910115238
Master length (cm)	55
Master width (cm)	33
Master height (cm)	38
Quantity in master	48
Master gross weight (kg)	10.400
ITF MASTER	28003910115235
How many pieces on 80x120 pallet (pz)	768
INTRASTAT Code	91070000
Country of origin	CHINA



Spina tripolare 16A
Presca tripolare bipasso 10/16A



MODALITA' D'USO

Programmazione:

La programmazione è semplice e si possono effettuare una o più programmazioni (fino a 96). Si procede modificando la posizione delle linguette che circondano la ghiera. Esse hanno 2 posizioni (su e giù); per ogni linguetta abbassata (fig. 1), si attiva il blocco di 15 min desiderato oppure, tirandola su, si disattiva. Nell'esempio in figura 1, sono state abbassate 4 linguette, quindi il dispositivo è stato programmato per attivarsi per 1 ora consecutiva (4 linguette x 15min l'una).

Impostare l'ora corrente:

Ruotare la ghiera in senso orario fino a far corrispondere l'ora corrente con la freccia. Ad esempio in figura 2 è stato impostato il programmatore alle ore 4.

Selezione di accensione manuale o programmata:

Portando il selettore rosso posto a lato della presa in posizione I (fig. 1), l'apparecchiatura collegata sarà sempre attiva; non si usa dunque la funzione di programmazione.

Portando il selettore rosso in posizione II (fig. 1) si attiva la programmazione e l'apparecchiatura controllata viene attivata/disattivata esattamente come da programma.

Non collegare mai apparecchiature con prese elettriche danneggiate. Non utilizzare la presa in luoghi umidi.

Inserire la presa dell'apparecchiatura da controllare nella presa programmabile (fig. 3). Connettere alla presa solo apparecchi conformi alle caratteristiche supportate (3680W max).

