



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	6	24



TECHNICAL DATA




Name	BRICK
Power supply	SOLAR
Power supply provided	YES
Type of power supply provided	SOLAR PANEL
Battery type	18650
Stack technology	LITHIUM-ION
Rated voltage (V)	3,7
Battery capacity (mAh)	3000
Batteries provided	(INCLUDED)
Power battery (Wh)	11.1
Battery class	9
Battery/battery weight (kg)	0.084
Charging time (h)	8
Maximum autonomy (h)	24
LED quantity	SMD LED
Lighting power (W)	6
Lumen	800
Light colour	4000K
Scope (m)	8
Light beam	DIFFUSE
LED lifespan (hours)	20000
Beam angle (°)	140°
Detection angle (°)	120
Sensing distance	6
Detector operation time	20
IP Protection	IP65
Insulation class	III
Color	DARK GREY
Material	PLASTIC - PC
Standards	UN3481
Warranty	2 YEARS
Width (mm)	230
Depth (mm)	95
Height (mm)	45
Net weight (Kg)	0.570

DESCRIPTION

Solar LED wall light made of UV-resistant polycarbonate and ABS; contemporary and extremely refined design; resistant to shock and atmospheric agents; the electronics are particularly resistant to water. Operation: The lamp charges during the day using solar radiation. 2 modes of use: 1) The lamp turns on automatically at night and maintains 50% brightness for 5 hours, after which (or when the battery charge is less than 30%), the lamp switches to energy-saving mode: the lamp automatically turns on at 100% brightness when motion is detected within a distance of ≤ 6 meters, then turns off after 20 seconds of no motion. 2) Motion Sensor Mode: The lamp automatically turns on at night at 100% brightness when it detects motion within a distance of ≤ 6 meters, then switches to 5% brightness after 20 seconds of no motion. The lamp features latest-generation SMD LEDs with a high-performance diffuser: the light is uniform; 4000K light: neither too warm nor too cold. Equipped with a 2.8W monocrystalline solar panel and a 3000mAh Li-Ion battery, it guarantees battery life of up to 2-3 nights (depending on the charge received during the day), far exceeding market standards. It can be fixed using wall plugs (provided). Dimensions: 230mm x 97mm x 42mm; easy to attach using two dowels.

LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	50
Pack width (mm)	235
Pack height (mm)	100
Packed product weight (kg)	0.640
Inner width (cm)	53
Inner height (cm)	31
Quantity in inner	6
Gross weight inner (kg)	12.000
ITF INNER	18003910113555
Master width (cm)	53
Master height (cm)	34
Quantity in master	24
Master gross weight (kg)	27.000
ITF MASTER	28003910113552
How many pieces on 80x120 pallet (pz)	384
INTRASTAT Code	94055000



Solar Charging

