



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	6	36



TECHNICAL DATA

Name	HOLDEN
Power supply	SOLAR
Power supply provided	YES
Type of power supply provided	SOLAR PANEL
How many batteries are used	1
Battery type	18650
Stack technology	LITHIUM-ION
Rated voltage (V)	3,7
Battery capacity (mAh)	2000
Batteries provided	(INCLUDED)
Power battery (Wh)	7.4
Battery class	9
Battery/battery weight (kg)	0.050
Charging time (h)	8
Maximum autonomy (h)	8
Lighting source	SMD LED
Lighting power (W)	7
Lumen	1000
Light colour	4000K
Light beam	DIFFUSE
Beam angle (°)	120°
Detection angle (°)	180
Sensing distance	5
Detector operation time	10 SECONDS
Installation height (m)	3-5 METERS
Switch	YES
IP Protection	IP54
Insulation class	III
Color	DARK GREY
Material	ABS + PC
Standards	UN3481
Warranty	2 YEARS
Width (mm)	119
Depth (mm)	144
Height (mm)	56
Net weight (Kg)	0.390

DESCRIPTION

Solar LED Wall Light: Classic, simple, beautiful. 1000 lumen solar LED outdoor light with motion sensor. Stunning lighting effects create a wonderful atmosphere in your front yard or garden. The light uses the latest-generation SMD LEDs with a high-performance diffuser: the light is uniform; 4000K light: not too warm, not too cold. Solar light: This solar light with motion sensor charges during the day with solar energy and lights up automatically in the dark or at night. It's solar-powered: no wiring required and uses free, eternally renewable energy. We recommend installing it in a sunny location to fully charge the batteries and enjoy a unique nighttime display! Solar LED wall light made of UV-resistant polycarbonate and ABS; contemporary and extremely refined design; IP44: resistant to shock and atmospheric agents; the electronics are particularly resistant to water. Operation: The lamp charges during the day using solar radiation. 4 modes: continuous lighting at 20% (motion sensor disabled); continuous lighting at 10% with motion sensor enabled; light off but motion sensor enabled; continuous lighting at 100% (motion sensor disabled). Equipped with a 2W monocrystalline solar panel and a 2000mAh Li-Ion battery that guarantees up to 8 hours of battery life (depending on the charge received during the day), far exceeding market standards. It can be mounted using wall plugs (provided).

LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	60
Pack width (mm)	130
Pack height (mm)	170
Packed product weight (kg)	0.446
Inner width (cm)	29
Inner length (cm)	27
Inner height (cm)	18
Quantity in inner	6
Gross weight inner (kg)	3.300
ITF INNER	18003910116075
Master length (cm)	62
Master width (cm)	29
Master height (cm)	37
Quantity in master	36
Master gross weight (kg)	21.000
ITF MASTER	28003910116072
How many pieces on 80x120 pallet (pz)	576
INTRASTAT Code	94055000
DEEE	0.08

