

DATA SHEET

LINER: 700-lumen solar LED wall light with double beam. Anthracite.



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	6	48



TECHNICAL DATA

Name	LINER
Power supply	SOLAR
Power supply provided	YES
Type of power supply provided	SOLAR PANEL
How many batteries are used	1
Battery type	18650
Stack technology	LITHIUM-ION
Rated voltage (V)	3,7
Battery capacity (mAh)	2000
Batteries provided	(INCLUDED)
Power battery (Wh)	7.4
Battery class	9
Battery/battery weight (kg)	0.050
Charging time (h)	8
Maximum autonomy (h)	8
Lighting source	SMD LED
Lighting power (W)	5
Lumen	700
Light colour	4000K
Light beam	DIFFUSE
Installation height (m)	3-5 METERS
Switch	YES
IP Protection	IP44
Insulation class	III
Color	DARK GREY
Material	ABS + PC
Standards	UN3481
Warranty	2 YEARS
Width (mm)	178
Depth (mm)	42
Height (mm)	63
Net weight (Kg)	0.180

DESCRIPTION

Solar LED Wall Light: Classic, simple, beautiful. This 700-lumen solar LED outdoor light features a dual beam, up-and-down effect, creating stunning lighting effects that create a wonderful atmosphere in your front yard or garden. The lamp uses the latest-generation SMD LEDs with a high-performance diffuser: the light is uniform; 4000K light: not too warm, not too cold. Solar light: This solar lamp with an Up & Down effect charges during the day with solar energy and lights up automatically in the dark or at night. It's solar-powered: no wiring required and uses free, eternally renewable energy. We recommend installing it in a particularly sunny area to fully charge the batteries and enjoy a unique nighttime display! Solar LED wall light made of UV-resistant polycarbonate and ABS; contemporary and extremely refined design; IP44: resistant to shock and atmospheric agents; the electronics are particularly resistant to water. Operation: The lamp charges during the day using solar radiation. It has 4 modes: continuous lighting at 25%, 50%, 75%, and 100%. It also allows you to manage battery life. Equipped with a 1.3W monocrystalline solar panel and a 2000mAh Li-Ion battery that guarantees up to 8 hours of battery life (depending on the charge received during the day), well above market standards. It can be mounted using wall plugs (provided).

LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	50
Pack width (mm)	180
Pack height (mm)	75
Packed product weight (kg)	0.224
Inner width (cm)	35
Inner length (cm)	20
Inner height (cm)	16
Quantity in inner	6
Gross weight inner (kg)	1.800
ITF INNER	18003910116143
Master length (cm)	43
Master width (cm)	35
Master height (cm)	34
Quantity in master	48
Master gross weight (kg)	15.000
ITF MASTER	28003910116140
INTRASTAT Code	94055000
DEEE	0.04

