



PACKING ☐ / ☒	INNER ☐ pcs	MASTER ☒ pcs
Colour Box	4	4



TECHNICAL DATA

Power supply	SOLAR
Power supply provided	YES
Type of power supply provided	SOLAR PANEL
Battery type	18650
Stack technology	LITHIUM-ION
Rated voltage (V)	3,7
Battery capacity (mAh)	2200
Batteries provided	(INCLUDED)
Power battery (Wh)	8.14
Battery class	9
Battery/battery weight (kg)	0.047
Charging time (h)	12
Maximum autonomy (h)	8
Lighting source	SMD LED
Lighting power (W)	6
Lumen	600
Light colour	4000K
Light beam	DIFFUSE
Lamp included	(INCLUDED)
Beam angle (°)	180°
Detection angle (°)	120°
Detector operation time	8 SECONDS
Extendable	NO
Switch	YES
IP Protection	IP44
Insulation class	III
Country of origin	CHINA
Material	METAL
Standards	UN3481
Warranty	2 YEARS
Width (mm)	158
Depth (mm)	158
Height (mm)	541
Net weight (Kg)	1.091

DESCRIPTION

Solar LED floor lamp in stainless steel; contemporary and extremely refined design; shock and weather resistant; the electronics are particularly resistant to water. Operation: The lamp recharges during the day using solar radiation. 3 modes: 1) Always on: The light automatically turns on at sunset for 8 hours. 20 lumens continuous: The lamp is then used as a streetlight; it will automatically turn off at dawn. 2) Mixed mode: The light automatically turns on at sunset: 20 lumens continuous; in addition, the motion detector activates: 400 lumens for 8 seconds if it detects motion; it will automatically turn off at dawn. 3) Detection only mode: The lamp will turn on for 8 seconds at 600 lumens if it detects motion in the covered area; it functions as both a courtesy light and a security light. The lamp features latest-generation SMD LEDs with a high-performance diffuser: the light is uniform; 4000K light: neither too warm nor too cold. Equipped with a 6V 0.3A monocrystalline solar panel and a 2200mAh Li-Ion battery; it can be fixed with wall plugs or using the convenient peg provided; battery life: up to 8 hours depending on the charge received during the day. Dimensions: 54 cm high and 16 cm in diameter.

LOGISTICS DATA

Packing type	Colour Box
Pack length (mm)	170
Pack width (mm)	170
Pack height (mm)	550
Packed product weight (kg)	1.388
Inner length (cm)	36
Inner height (cm)	50
Quantity in inner	4
Gross weight inner (kg)	6.300
ITF INNER	18003910108247
Quantity in master	4
How many pieces on 80x120 pallet (pz)	48
INTRASTAT Code	94055000
DEEE	0.21
ECOLOGIC SCALES 2025	MLUMI030000
Country of origin	CHINA



ø 160 mm



3 MODES:

- A ALWAYS ON**
20 Lm
- B ON + PIR**
20 Lm + 400 Lm x 8 sec
- C OFF + PIR**
OFF + 600 Lm x 8 sec

2 MODI PER INSTALLARE / 2 WAYS OF INSTALLATION




USE IN THE GARDENS



(Spike included)



USE IN THE FLOORS



(3 Screws included)

