



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	4	24



TECHNICAL DATA


Name	SUGAR
Power supply	SOLAR
Power supply provided	YES
Type of power supply provided	SOLAR PANEL
How many batteries are used	1
Battery type	18650
Stack technology	LITHIUM-ION
Rated voltage (V)	3,7
Battery capacity (mAh)	2000
Batteries provided	(INCLUDED)
Power battery (Wh)	7.4
Battery class	9
Battery/battery weight (kg)	0.050
Charging time (h)	8
Maximum autonomy (h)	8
Lighting source	SMD LED
Lighting power (W)	14
Lumen	2000
Light colour	4000K
Light beam	DIFFUSE
Beam angle (°)	270°
Detection angle (°)	180
Sensing distance	5
Detector operation time	10 SECONDS
Installation height (m)	3-5 METERS
Switch	YES
IP Protection	IP44
Insulation class	III
Color	WHITE
Material	ABS + PC
Standards	UN3481
Warranty	2 YEARS
Width (mm)	114
Depth (mm)	107
Height (mm)	149
Net weight (Kg)	0.360

DESCRIPTION


Solar LED wall light: Classic, simple, beautiful. 2000 lumen solar LED outdoor light with motion sensor. Compact and adjustable light: illuminates every corner! The lamp uses latest-generation SMD LEDs with a high-performance diffuser: the light is uniform; 4000K light: not too warm, not too cold. Solar light: This solar light with motion sensor charges during the day with solar energy and lights up automatically in the dark or at night. It's solar-powered: no wiring required and uses free, eternally renewable energy. We recommend installing it in a sunny location to fully charge the batteries and enjoy a unique nighttime display! Solar LED spotlight made of UV-resistant polycarbonate and ABS; contemporary and extremely refined design; IP44: resistant to shock and atmospheric agents; the electronics are particularly resistant to water. Operation: The lamp charges during the day using solar radiation. 4 modes: continuous lighting 50 lumens + motion sensor (2000 lumens for 10 seconds); light off but motion sensor active (2000 lumens for 10 seconds); continuous lighting 50 lumens (motion sensor disabled). Equipped with a 1W monocrystalline solar panel and a 2000mAh Li-Ion battery that guarantees up to 8 hours of battery life (depending on the charge received during the day), well above market standards. It can be mounted using wall plugs (provided).

LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	115
Pack width (mm)	130
Pack height (mm)	150
Packed product weight (kg)	0.470
Inner width (cm)	30
Inner length (cm)	36
Inner height (cm)	17
Quantity in inner	4
Gross weight inner (kg)	3.000
ITF INNER	18003910116105
Master length (cm)	78
Master width (cm)	30
Master height (cm)	35
Quantity in master	24
Master gross weight (kg)	13.000
ITF MASTER	28003910116102
How many pieces on 80x120 pallet (pz)	288
INTRASTAT Code	94055000
DEEE	0.08



Spostamento orizzontale
Moving horizontally



Scorrimento verticale
Vertical sliding

