



PACKING 	INNER pcs	MASTER pcs
Brown Box	1	10



## TECHNICAL DATA

Power supply	RECHARGEABLE BATTERIES
Power supply provided	YES
Type of power supply provided	AC/DC ADAPTOR
How many batteries are used	1
Battery type	18650
Stack technology	LITHIUM-ION
Rated voltage (V)	3,7
Battery capacity (mAh)	1960
Batteries provided	(INCLUDED)
Power battery (Wh)	7.252
Battery class	9
Battery/battery weight (kg)	0.042
Charging time (h)	6
Maximum autonomy (h)	50
Lighting source	HIGH POWER LED
Light technology	CREE®-XP-G3
Lighting power (W)	5
Lumen	300
Scope (m)	300
Light beam	FOCUS
LED lifespan (hours)	50.000
Beam angle (°)	30°
Switch	YES
Maximum beam intensity (Cd)	9732
Plug	Type C/EF - 2 pin (Europlug/FR-DE Hybrid WITHOUT EARTH)
IP Protection	IP64
Insulation class	III
Color	YELLOW
Country of origin	CHINA
Material	PLASTIC - PC
Standards	UN3481
Warranty	2 YEARS
Width (mm)	260
Depth (mm)	150
Height (mm)	175
Net weight (Kg)	1.004

## DESCRIPTION

Powerful: Spot Ex is a very powerful handheld spotlight: 5W (XP-G3 CREE), 300 real lumens; Aircraft grade aluminum heatsink for better heat dissipation. Range: 300 m, 30° focused light, high performance Velamp reflector. Autonomous; Central LED: up to 50 hours (20% light). 16 hours for 50% light. 4 hours for 100° light; the headlight is equipped with a 3.7V 2Ah 18650 Li-Ion battery; recharges in 6 hours; includes: 220V adapter, wall charging base. ATEX: ATEX zone 0 certified. Durable: Made of polycarbonate and ABS; IP64: water resistant.

## LOGISTICS DATA

Packing type	Brown Box
Pack length (mm)	150
Pack width (mm)	300
Pack height (mm)	180
Packed product weight (kg)	1.325
Inner length (cm)	76
Inner height (cm)	39
Quantity in inner	1
Gross weight inner (kg)	14.430
ITF INNER	18003910106755
Quantity in master	10
How many pieces on 80x120 pallet (pz)	120
INTRASTAT Code	85131000
DEEE	0.21
ECOLOGIC SCALES 2025	MLUMI030000
Country of origin	CHINA



	Class I Div 1&2 Grp ABCD / Class II Div 1&2 Grp EFG Class III / Temperature Code T4 IP64 File number: 261379
	Gas: II 1G Ex ia op is IIC T4 Ga (Zone 0) Mine: I M1 Ex ia op is I Ma SIRA 17 ATEX 2195X
	Gas: Ex ia op is IIC T4 Ga (Zone 0) Mine: Ex ia op is I Ma IECEx SIR 17.0042X
	0518