



PACKING 	INNER pcs	MASTER pcs
Shrink	12	12



## TECHNICAL DATA

Power supply	DRY BATTERIES
Power supply provided	NO
How many batteries are used	2
Battery type	4R25
Batteries provided	(NOT INCLUDED)
Maximum autonomy (h)	900
Lighting source	STANDARD LED
Light beam	DIFFUSE
LED lifespan (hours)	30.000
Switch	YES
Functions	BLINK LIGHT / STEADY LIGHT
IP Protection	IP44
Color	YELLOW
Country of origin	CHINA
Material	PLASTIC - PC
Handbook	<a href="https://www.velamp.com/manuali/ST088_manuale.pdf">https://www.velamp.com/manuali/ST088_manuale.pdf</a>
Warranty	2 YEARS
Width (mm)	180
Depth (mm)	85
Height (mm)	360
Net weight (Kg)	0.534

## DESCRIPTION

Fluorescent yellow body and red diffuser; all in polycarbonate highly resistant to shocks, UV and atmospheric conditions. Equipped with a diffuser specially designed for high visibility of the flash both day and night. Choice between "flash" (flashing) or "steady" (steady, non-flashing light) mode. Adjustable hot-dip galvanized metal mounting bracket; works with 1 or 2 4R25 batteries (or one 4R25-2), not supplied.

## LOGISTICS DATA

Packing type	Shrink
Pack length (mm)	85
Pack width (mm)	180
Pack height (mm)	360
Packed product weight (kg)	0.550
Inner length (cm)	52
Inner height (cm)	38
Quantity in inner	12

## LOGISTICS DATA

Gross weight inner (kg)	7.410
ITF INNER	18003910110523
Quantity in master	12
How many pieces on 80x120 pallet (pz)	144
INTRASTAT Code	85308000
DEEE	0.11
ECOLOGIC SCALES 2025	MLUMI030000
Country of origin	CHINA



Optional :  
**KEY08**  
(not included)



**Multifunction key**



WORKS WITH:

1 x 4R25



Or

2 x 4R25



Or

1x 4r25-2

