



PACKING 	INNER 	MASTER
Shrink	6	6



TECHNICAL DATA

Power supply	SOLAR
Power supply provided	YES
Type of power supply provided	SOLAR PANEL
How many batteries are used	1
Battery type	AA
Stack technology	NI-MH
Rated voltage (V)	1.2
Battery capacity (mAh)	1500
Batteries provided	(INCLUDED)
Power battery (Wh)	1.8
Battery class	9
Battery/battery weight (kg)	0.005
Charging time (h)	8
Maximum autonomy (h)	90
LED quantity	2
Lighting source	STANDARD LED
LED lifespan (hours)	30.000
Switch	YES
Functions	BLINK LIGHT / STEADY LIGHT
IP Protection	IP44
Insulation class	III
Color	YELLOW
Country of origin	CHINA
Material	PLASTIC - PC
Standards	UN3496
Handbook	https://www.velamp.com/manuali/ST089_manuali.pdf
Warranty	2 YEARS
Width (mm)	340
Depth (mm)	190
Height (mm)	80
Net weight (Kg)	0.600

DESCRIPTION

2-LED street light. With twilight sensor. Flashing light. 90-hour battery life. Fluorescent yellow body and orange diffuser; all made of highly impact-, UV-, and weather-resistant polycarbonate. Adjustable mounting bracket and hot-dip galvanized metal handle. Equipped with a diffuser specially designed for high visibility of the flash both day and night. With twilight sensor: the lamp turns on automatically at night and turns off automatically during the day. Operation: The flashing light is powered by a rechargeable 1.2V 1500mAh Ni-MH battery. It charges during the day with sunlight and automatically turns on at night to flash. You don't have to worry about anything! It will turn off automatically to recharge.

LOGISTICS DATA

Packing type	Shrink
Pack length (mm)	190
Pack width (mm)	340
Pack height (mm)	80
Packed product weight (kg)	0.670
Inner length (cm)	52
Inner height (cm)	21
Quantity in inner	6
Gross weight inner (kg)	4.600
ITF INNER	18003910113081
Quantity in master	6
How many pieces on 80x120 pallet (pz)	168
INTRASTAT Code	85308000
ECOLOGIC SCALES 2025	MLUMI030000
Country of origin	CHINA



Solar Charging



Optional :
KEY08
(not included)



Multifunction key

