



PACKING ☐ / ☑	INNER ☐ pcs	MASTER ☐ pcs
Colour Box	2	8



TECHNICAL DATA

Power supply	RECHARGEABLE BATTERIES
Power supply provided	YES
Type of power supply provided	AC/DC ADAPTOR +12V CAR ADAPTOR
Battery type	18650
Stack technology	LITHIUM-ION
Rated voltage (V)	7,4
Battery capacity (mAh)	8000
Batteries provided	(INCLUDED)
Power battery (Wh)	59.2
Battery class	9
Battery/battery weight (kg)	0.362
Charging time (h)	4.5
Maximum autonomy (h)	3
Lighting source	2835 SMD LED
Lighting power (W)	50
Lumen	3600
Light colour	6500K
Scope (m)	25
Light beam	DIFFUSE
LED lifespan (hours)	30.000
Beam angle (°)	100°
Switch	YES
Functions	POWERBANK
Plug	Type C/EF - 2 pin (Europlug/FR-DE Hybrid)
IP Protection	IP65
Mechanical strength (IK)	IK08
Insulation class	III
Color	YELLOW
Country of origin	CHINA
Material	PLASTIC - PC
Standards	UN3481
Warranty	2 YEARS
Width (mm)	255
Depth (mm)	90
Height (mm)	230
Net weight (Kg)	1.860

DESCRIPTION

Power: X-Blast 50W is a rechargeable construction site floodlight that uses SMD LEDs. 50W and 3600 real lumens: a real light on your construction site; Aircraft-grade aluminum heatsink for better heat dissipation. Diffuser: X-Blast is a floodlight projector; it is therefore used to illuminate a surface such as a wall or a room; polycarbonate diffuser and 120° high-performance reflector for shadow-free and uniform light; 6500K light. Autonomous. 3 hours of guaranteed light at full power; quick recharge in 4.5 hours thanks to the special transformer included; the projector is equipped with a 7.4V 8Ah 18650 Li-Ion battery with charge indicator; 220V and 12V chargers included. X-Blast can be installed on any tripod; the swivel mount allows you to adjust the light as needed and to transport the projector anywhere, with minimal space; convenient ON/OFF switch; practical 2A output power bank to quickly charge your phone on the construction site. X-Blast is ultra-resistant and is resistant to jets of water according to the IP65 protection class; the body is made of polycarbonate with PVC reinforcements for better impact resistance (IK08), the glass is shockproof and the power cable is fixed with a special thread in the body; even in case of rain X-Blast continues to illuminate the surrounding environment without any problem.

LOGISTICS DATA

Packing type	Colour Box
Pack length (mm)	90
Pack width (mm)	255
Pack height (mm)	230
Packed product weight (kg)	2.060
Inner width (cm)	29
Inner length (cm)	26
Inner height (cm)	24
Quantity in inner	2
Gross weight inner (kg)	4.200
ITF INNER	18003910112596
Master length (cm)	50
Master width (cm)	29
Master height (cm)	38
Quantity in master	8
Master gross weight (kg)	17.400
ITF MASTER	28003910112593
How many pieces on 80x120 pallet (pz)	192
INTRASTAT Code	94054210
ECOLOGIC SCALES 2025	MLUMI030000
Country of origin	CHINA



Scopri tutte le sue potenzialità!

ROBUSTO
Corso in morbido PVC protegge la lampada

TOUGH
Soft PVC sleeve protects light from damage

ROBUSTO
Corpo in policarbonato. Assemblaggio IP68. Waterproof-IP68

ROBUST
Strong polycarbonate body absorbs shocks IP68 waterproof-IP68

DISSIPATORE DI CALORE
Ad alto rendimento assicura la durata a vita del led

HIGH PERFORMANCE HEAT SINK
Ensures LED life span

MULTIUSO
Staffa di fissaggio universale e maniglia girevole in policarbonato per il trasporto

MULTI USE
Universal fixing bracket and swivel handle for carrying. Polycarbonate material increases strength

LUCE IPER POTENTE
LED OSRAM® 2835 SMD

HIGH PERFORMANCE LIGHT
OSRAM® 2835 SMD LED

INFRANGIBILE
Lente in policarbonato

SHATTER PROOF
Polycarbonate lens

