



PACKING	INNER	MASTER
/	pcs	pcs
Plastic hanger	6	36



## TECHNICAL DATA

Power supply	220V AC
Power supply provided	YES
Type of power supply provided	POWER CABLE
Cable section	H05RR-F 3G1.5mm <sup>2</sup>
Cable length (meters)	1,5
Switch	YES
Functions	ON/OFF
Plug	Type E / F - 2 pin (EU Hybrid)
Main socket	French type 2P+T
Number of sockets	3
Maximum load	3680W
IP Protection	IP44
Insulation class	I
Color	BLACK
Material	PLASTIC-OTHER
NF	YES
Warranty	2 YEARS
Width (mm)	320
Depth (mm)	80
Height (mm)	60
Net weight (Kg)	0.415

## DESCRIPTION

3-way 2P+T IP44 power strip with Type E/F plug - 2 pin (EU Hybrid) - Ensures a safe and stable connection up to 3680W of power. - 1.5 m neoprene cable and switch. 3680W power, robust and safe, ideal for workshops and outdoor use. 3-SOCKET MULTI-SOCKET IP44 – Electrical strip with 3 French-style 2P+T sockets and IP44 protection, ideal for outdoor environments, workshops, gardens and construction sites. Type E / F PLUG - 2 pin (EU Hybrid) – Ensures a safe and stable connection up to 3680W of power. H05RR-F 3G1.5 NEOPRENE CABLE – 1.5 meters long, resistant to twisting, moisture, and abrasion. Perfect for intensive and professional use. INTEGRATED SWITCH – Allows you to easily turn connected devices on and off without unplugging them.

## LOGISTICS DATA

Packing type	Plastic hanger
Pack length (mm)	80
Pack width (mm)	320
Pack height (mm)	60
Packed product weight (kg)	0.415

## LOGISTICS DATA

Inner width (cm)	34
Inner length (cm)	57
Inner height (cm)	6
Quantity in inner	6
Gross weight inner (kg)	2.500
ITF INNER	18003910116938
Master length (cm)	62
Master width (cm)	34
Master height (cm)	28
Quantity in master	36
Master gross weight (kg)	15.900
ITF MASTER	28003910116935
How many pieces on 80x120 pallet (pz)	432
INTRASTAT Code	85366190
DEEE	0.03



Multiprise standard français  
French standard multisocket



Pays compatibles:   
Compatible countries:

**16A - 2 pôles + terre**  
**250V - 3680W max**



**CÂBLES EN CUIVRE ÉPAIS POUR UNE PARFAITE SÉCURITÉ**

Velamp utilise des fils en vrai cuivre qui garantissent une bonne conductivité électrique et une excellente dispersion de la chaleur. La gaine en PVC est ultra résistante.

