



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	1	1



TECHNICAL DATA

Name	Ribbon 50
Power supply	220V AC
Power supply provided	YES
Type of power supply provided	POWER CABLE
Lighting source	2835 SMD LED
Lighting power (W)	610
Electricity consumption (W)	610
Lumen	65000
IRC	>90.4
Light colour	4000K
Light beam	DIFFUSE
LED lifespan (hours)	30000
Extendable	NO
Power cord length (cm)	150
Cable section	H05RN-F 2x1.0mm ²
Switch	NO
Functions	ON / OFF
Plug	Type E / F - 2 pin (EU Hybrid)
IP Protection	IP65
Insulation class	II
Dimmability	NOT DIMMABLE
Color	WHITE
Country of origin	CHINA
Material	PLASTIC - OTHER
Energy class	F
Warranty	2 YEARS
Width (mm)	350
Depth (mm)	250
Height (mm)	420
Net weight (Kg)	9.470

DESCRIPTION

Extremely bright: the strip can be installed in a flash anywhere. Once unrolled, it lights up: 65,000 lumens of light (610W) illuminate the construction site, the warehouse, the garden... And it's a very powerful light. Rolled up on its convenient reel, it's 50 meters long and very easy to transport and store. **WARNING:** The strip must be completely unrolled during use! IP65 waterproof: splash-proof. The light functions normally when it rains. Ideal for construction sites, but also for all outdoor activities such as markets, stands, outdoor parties, and emergency situations. Robust: temperature-resistant: it works flawlessly from -10°C to +40°C. Natural light 4000K. The power cable is 1.5 metres long and is equipped with a European CEE 7/7 (schuko) plug.

LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	280
Pack width (mm)	370
Pack height (mm)	450
Packed product weight (kg)	10.150
Quantity in inner	1
Quantity in master	1
How many pieces on 80x120 pallet (pz)	32
INTRASTAT Code	85395200
DEEE	0.48
ECOLOGIC SCALES 2025	MLUMI040000
Country of origin	CHINA

