



PACKING	INNER	MASTER
/	pcs	pcs
<b>Colour box</b>	<b>4</b>	<b>4</b>



## TECHNICAL DATA

Name	MARSHALL
Power supply	220V AC
Power supply provided	YES
Type of power supply provided	POWER CABLE
Electricity consumption (W)	2000
Power cord length (cm)	140
Cable section	H05RN-F 3G1.0mm2
Switch	YES
Functions	HOT + FAN
Absorption (A)	8,3-9,1
Plug	Type E / F - 2 pin (EU Hybrid)
Power adjustment (W)	22W/1000W/2000W
Timer	NO
Fuse required	YES
Auto reset thermostat	YES
Volume of hot air generated (m³h)	140
Heating area (m²)	20
Operating temperature (°C)	-15°C + 25°C
IP Protection	IP20
Insulation class	I
Fuse	10A
Color	BLACK
Country of origin	CHINA
Material	PLASTIC + METAL
Warranty	2 YEARS
Width (mm)	210
Depth (mm)	130
Height (mm)	260
Net weight (Kg)	1.530

## DESCRIPTION

2000W hot air generator; ceramic technology: unlike coil models, ceramic models heat up quickly; the "cannon" shape ensures better airflow direction. Excellent for temporarily heating a 20m2 room; useful for drying plaster. With fan function. Temperature regulation (25/1000/2000W), heats 140m3/h; with safety thermostat (triggers at 70°). Equipped with a 140cm cable with a CEE 7/7 (Schuko) socket; highly resistant metal structure; IPX0; operating temperature: -15°C / +25°C.

## LOGISTICS DATA

Packing type	Colour box
Pack length (mm)	180
Pack width (mm)	260
Pack height (mm)	310
Packed product weight (kg)	1.900
Inner length (cm)	38
Inner height (cm)	63
Quantity in inner	4
Gross weight inner (kg)	8.400
ITF INNER	18003910114453
Quantity in master	4
How many pieces on 80x120 pallet (pz)	76
INTRASTAT Code	85162991
DEEE	0.21
ECOLOGIC SCALES 2025	MCHAE010000
Country of origin	CHINA



### FUNZIONI FUNCTIONS



SCHUKO  
220/240V  
2000W

1,4m

